

**Datasheet**



**goldilock**

**1100 Series Datasheet**





## Specification

### Physical Interface

<b>Connectors</b>	12 x RJ45 Ethernet Port Pairs
<b>Performance</b>	Goldilock Drawbridge operates at the physical layer, so no bitrate throttling occurs. All performance speeds would be determined by the external throughput of the connected devices.
<b>Technology</b>	Ethernet – Physical Layer (OSI Layer 1)

### Management

<b>Interface</b>	Out-of-Band(OOB) Ethernet Port, RJ45, 1GbE
<b>Console/UI</b>	Built-in browser-based administration console
<b>Protocols</b>	HTTP/HTTPS
<b>UI Security</b>	Password Protected, Multi-factor Authentication, Logging, Brute Force Detection
<b>Other Features</b>	Live status dashboard, manual port control, scheduled port control events, SMS user management, management network settings, configuration backup/import, offline update system



## Remote Triggers

<b>Interface</b>	SMS via 4G LTE, GPRS, or GSM cellular signal
<b>Antenna</b>	2 x SMA (Female) connectors
<b>SIM</b>	1 x SIM slot (Standard size, 25mm x 15mm x 0.76mm)
<b>Authentication</b>	Structured Command, Number filtering, Multi-factor Authentication, Spam/SMS Bomb protection, Granular Port Control

## Mechanical

<b>Form Factor</b>	1U Rackmount
<b>Dimensions</b>	W480mm x D295mm x H41.6mm
<b>Weight</b>	4.5KG
<b>Mounting</b>	Rackmount, front-mounted ears
<b>Enclosure</b>	Cold rolled steel, powder coated (Sandtex Graphite)
<b>Cooling</b>	Passive, Fanless

## Power

<b>Input</b>	110 to 240V AC, 50/60Hz
<b>Power Consumption</b>	15W peak, 10W average
<b>Connector</b>	IEC C14



## Environmental




<b>Operating Temperature</b>	-20C to +50C (-4F to +122F)
<b>Storage Temperature</b>	-40C to +80C (-40F to +176F)
<b>Operating Humidity</b>	0 to 95% (non-condensing)
<b>Storage humidity</b>	0 to 95% (non-condensing)
<b>Shock</b>	IEC 60068-2-27
<b>Freefall</b>	IEC 60068-2-32
<b>Vibration</b>	IEC 60068-2-6

## Safety

<b>EMI</b>	CE, UKCA, FCC Part B Class A
<b>EMS</b>	EN 61000-4-2/3/4/5/6/8, CISPR 32, FCC Part B Class A
<b>Operating Humidity</b>	0 to 95% (non-condensing)



## Mechanical Drawing



## Package Contents

- 1 x Goldilock GL-1100 series device
- 2 x SMA 4G Antennas
- 1 x IEC C13 Power Cable

## Ordering Information

SKU	Description
GL-1111	1U Rackmount, 12 Port Pairs, AC Power, Remote SMS Trigger